

Declaration of Performance

Nr 04-002

1. Unique identification code of the product type

Profiline fasterners and fixings with acoustic rubber (Appendix 1)

2. Type, batch or serial number or any other element allowing identification of the product

Product name and date of manufacture: on the product or on the product packaging

3. Intended use of the product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer

Metal framing components for gypsum board systems

4. Declared performance

LEDEN ESTONIA AS Loovälja tee 11 74207 Liivamäe küla Jõelähtme vald Harjumaa Estonia

5. Authorized representative

Not applicable

- System of assessment and verification of constant performance of the product System 4
- 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard

Standard EN 13964:2014

8. European technical assessment

Not applicable

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification	
Zinc coating	Z>100	EN 10326;EN 10 327	
Reaction to fire	A2	EN 13964:2014 96/603/EC	
Durability	Class B	EN 13964:2014	
Permissible load	rmissible load Appendix 1		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Liivamäe, 25.10.2024

Janek Tabun Member of the Board

Mee

Appendix 1

Code number	Product name	Material thickness	Permissible load [kN]	Maximum load tested [kN]
CD 14 akust	Profile brackets with acoustic rubber 60/120mm	0,8 mm	0,40	2,1
CD 20 akust	Profile brackets with acoustic rubber 60/200mm	0,8 mm	0,40	2,1
JR 640 akust	Nonius hanger – upper part 640mm	1,0 mm	0,40	1,149
JR 940 akust	Nonius hanger – upper part 940mm	1,0 mm	0,40	1,149
JR xxx akust	Nonius hanger – upper part Other length variations	1,0 mm	0,40	1,149
RS 375akust	Suspension wire with eyelet 6mm 375mm	Ø4 mm	0,50	1,335
RS 500akust	Suspension wire with eyelet 6mm 500mm	Ø4 mm	0,50	1,335
RS 750akust	Suspension wire with eyelet 6mm 750mm	Ø4 mm	0,50	1,335
RS XXXakust	Suspension wire with eyelet 6mm Other length variations	Ø4 mm	0,50	1,335

Me