


SKE horizontal profile

58mm



CE marked according to EN 14195 : 2014

DISCRIPTION:

SKE 58 horizontal profile is made of hot-dip galvanized steel. The profiles have 58 mm high flanges.

The profiles are equipped with two EPDM seals on the bottom, which ensure an effective sound dampening effect.

A roughness is rolled into the edges, which simplifies the installation of screws.

At the bottom of the profile there are evenly spaced holes for screw fasteners.

The profiles are bundled with plastic tape and packed on pallets.

PRODUCT	LENGTH mm	BUNDLE pc	PALLET pc
SKE66/58	3000; 3600	4	64
SKE70/58	3000; 3600	4	64
SKE95/58	3000; 3600	4	48
SKE120/58	3000; 3600	4	48

PERFORMANCE

Fire class	A1
Braking strength	270 – 500 MPa
Hazardous substances	NPD
Environment class	C1
Material	Steel DX51D
Coating	Zink 100 Gr/m ²

USAGE:

SKE 58 horizontal profile is used as a lower or upper runner together with Profiline AVP acoustic vertical profiles for the construction of a steel frame of partition walls with increased sound absorption requirements.

If necessary, the profiles can be cut to size with sheet metal scissors or a hacksaw.

Profiles can be stored in a dry and clean environment.

Steel scraps are 100% recyclable.

PRODUCT	A	B	C
SKE66/58	58	66	58
SKE70/58	58	70	58
SKE95/58	58	95	58
SKE120/58	58	120	58